

# /strata geotech

# Rocprop<sup>®</sup> Mechanical Roof Prop

The Rocprop<sup>®</sup> is a compact, all-steel roof support prop for underground mining that offers active pre-loading. It provides constant load characteristics over a large closure range and at high convergence rates.

- Rocprop is ideal for use in coal, hard rock and soft rock mining environments
- Active support is achieved using hydraulic pre-loading
- Can be installed at an angle or horizontally
- Easy to transport and install, offering significant savings in materials handling
- Usable anywhere there is access to hydraulic, emulsion or water supply



# COAL MINING ROOF SUPPORT

- Available in a selection of sizes and in 20 ton and 40 ton variations
- Variety of headboards and footplates to distribute the load and prevent punching through
- Provide a workable solution for roadways and beltdrive support, as well as during longwall moves
- No ventilation resistance

### HARD ROCK MINING ROOF SUPPORT

- High load-bearing capabilities make it suitable for high closure and seismic mining environments
- Provide constant hanging roof support to keep blocks in place during blasting
- Ideal for long term support in isolated, abandoned and high cavity areas
- Available in heights up to 20 feet

/strata geotech

24

WEIGHT

lbs.

78

160

186

211

270 69

92

113

121

148

Rocprop 40 ton unit

Rocprop 20 ton unit

DISPLACEMENT (inches)

## **APPLICATIONS IN COAL AND OTHER SOFT ROCK MINES**

- Longwall moves (shield recovery)
- · Belt drive support
- Brow support
- Systematic roadway support
- Tailgate, headgate and bleeder support
- Barrier line support
- Ventilation seal construction
- Long-term support in abandoned areas

### **BENEFITS**

- Quick and easy to install
- · Installed vertical, horizontal and at an angle
- Creates pre-loading up to 20 tons
- Dynamic yield capacity
- Heights up to 20 feet
- · Support applied exactly where needed
- · Variety of accessories available

#### Headplates



Flat



Channel



Pizza

YIELD

Load in

Tons

22

22

22

22

22

44

44

44

44

44

TRANSPORT

LENGTH

Inches

42

87

113

113

145

36

50

61

66

81





Cone Setting Tool

Hose Assembly



#### **USA**

8800 Roswell Road, Suite 145 Sandy Springs, GA 30350 USA TF: 800-691-6601 T: 770-321-2500 T: 724-745-5030 info@strataworldwide.com

#### CANADA

Ontario North Bay, Ontario Canada Tel: (705) 978 2304

44 87 91 138 160 Footplate Accessories

14 16 18 20 22

47

90

112

122

169

39

55

67

71

83

MINING HEIGHT Min. Inches | Max. Inches

59

137

157

177

236

47

71

91

98

126

**ROCPROP® PERFORMANCE** 

60

50

40

30

20

10

0

PRODUCT

Code

RP1520

RP3520

RP4020

RP4520

RP6020

RP1240

RP1840

RP2340

RP2540

RP3240

RP3540

FORCE (tons)



www.strataworldwide.com/mining