

# Sand Prop™

Fast, easy installation

The Sand Prop™ is a compact, self-contained high-capacity prop designed to be easily installed.

- Sand Prop™ has a capacity of 60 tons
- Can provide up to 2 inches of deformation before buckling
- Available in lengths from 4 to 9 feet
- Each unit has 2 feet of height adjustment
- The ease of installation allows for quick placement and less labor requirements, which in turn increases productivity
- Can be reused by removing the wedges and recharging the sand into the upper unit. Do not remove under load
- A variety of headplate and footplate designs are available for special applications

## FEATURES & BENEFITS

- Lightweight
- One person installation
- High capacity
- Low cost
- No power tools required



# Sand Prop™

Fast, easy installation

## APPLICATIONS

- Tailgate and bleeder support
- X-Cut and intersection stabilization
- Belt line entry support
- Longwall shield recovery



Product Code	Load	Height Range		Weight
		Closed	Open	
SAND4-6	60 tons	4 ft.	6 ft.	83 lbs.
SAND5-7	60 tons	5 ft.	7 ft.	91 lbs.
SAND6-8	60 tons	6 ft.	8 ft.	99 lbs.
SAND7-9	60 tons	7 ft.	9 ft.	105 lbs.

Other sizes may be available.

## SAND PROP™ Performance

